

# Low Smoke & Fume

## Copper Clad Aluminium Magnesium (CCAM) Cable

# CQR

First choice for quality

A cable designed by CQR to meet all aspects of the European Construction Product Regulation (CPR) EN50575.

This cable has been independently tested and certified by an accredited test facility and has been awarded a CPR Euro classification.

CQR offer the Installer, Specifier and End User a quality cabling solution and piece of mind that the product will perform to specification in the event of a fire.


DoP Certificates available online for download



- Suitable for domestic applications and shorter distances
- 7 x 0.2mm Copper Clad Aluminium (CCAM)
- Low Smoke & Fume Jacket
- Manufactured to BS4737-3.30:2015 Type 3
- Fully compliant with EN50575 'CPR'

Also available with a PVC Sheath

### Available Cores



### Product codes

Code	Description
CABCCA8/WH/LSF/100	8 Cores LSF CCAM White 100m Reel

### Technical data

Core:	7 x 0.2mm
Resistance:	147.9 Ohms/Km
AWG:	24
Conductor Material:	Copper Clad Aluminium Magnesium (CCAM)
Conductor area:	0.22mm <sup>2</sup>
Max voltage:	50 volts
Sheathing:	LSF
Core insulation:	PVC
Operating temp:	70°C
Euroclass Rating:	E <sub>ca</sub>
SCREENED CABLE	
Drain wire:	Soft tinned copper
Screen:	Alu/Polyester Foil

rev. 3-11/2020



www.cqr.co.uk

info@cqr.co.uk

Sales: +(0)151 606 1000 Tech: +(0)151 606 6311

CQR Security Ltd, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK

Over 30 Years experience of alarm cable manufacturing in the United Kingdom

