

EPA-NG/PLUS

Electronic Hold Up Devices

The EPA - NG is the most advanced Hold-Up device available on the market today. Packed with innovative features, this electronic unit is a versatile device capable of many functions.



- Second Relay Output (for confirmed operation)
 - One or Two Button Operation
 - Timed Delay Operation
 - LED Indicator
 - Latching or Non Latching
 - Selectable EOL Settings
 - Keyless Reset
 - PD6662:2010 BS8243:2010

Specifications

	EPA-NG/PLUS
Connections	10 PCB Terminals
Operation Method	Single or Dual Push Button
Material	ABS
Dimensions mm	85 x 85 x 39
PA Output	Programmable Latching / Non Latching Relay
Voltage	12v DC
Current	10mA @ 12Vdc
Tamper	Cover
Reset Method	Dual Push
Colours	White, Stainless Steel, Brass
Standards	EN50131-1 Grade 3 & PD6662:2010 / BS8243:2010
Environmental Class	II



Contact us:

Phone:

Tel: +44(0)151 6061000
Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk
Email: info@cqr.co.uk



Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

