

Double push range of PA Buttons are suitable for use in Grade 3 Installations. Inside the traditional double push design are a selection of end-of-line resistors for the convenience of the installer.



First choice for quality



- Latching / non-latching
- Selectable for Normally Open / Normally Closed
- Indicator to show activation
- Microswitch Alarm and Tamper
- Selectable End of Line Resistors
- Key Resettable
- Spare keys available

rev. 2-11/2018	Product codes		Technical data	
-11/2	Code	Description _	Case Material	ABS or ABS /304 Grade Stainless Steel
018	PADP3/BS/BK	Brass Effect PA Button	Buttons	Acetal
			Reset Key	Steel
			Dimensions mm	75mm x 62mm x 29.5mm
			Operation	2 button, latching / no latching
			Reset Method	Кеу
			¥	3A 50Vdc changeover
			Anti Tamper	Normally closed tactile 24v DC at 1A max
				EN50131-1:2006 + A1:2009 Grade 3
🕒 in		-	Environmental Class	11
www.co	qr.co.uk			
info@cc	qr.co.uk			
🔁 Sales: +	-(0)151 606 1000	Tech: +(0)151 606 6311		
CQR Fire & Se	curity, 125 Pasture R	oad, Moreton, Wirral, CH46 4TH, UK	SGS_	bitish security industry association Fire Industry Association GROUP OF COMPANIES