

Unit 6,The Cedar Business Centre Avon Road, Cannock, Staffs WS11 1QJ Tel: +44 (0)1543 501 600 Fax: +44 (0)1543 501 601

Manufacturer's Declaration of Conformance

We declare that the following product:-

BS 5 Lever Mortice Sash Lock (SKSB2 / SKSS2 / SKSB3 / SKSS3)

have been successfully tested to:-

BS EN12209 : 2003 & BS3621: 2007



Code	Classification	Category
1	Category of Use	Medium Frequency of Use by people with incentive to
-		exercise care, but with some chance of mis-use
2	Durability	200,000 Cycles with 120N load force on Latch bolt
3	Door Mass	For Doors up to 200 kg with 25N Closing Force
4	Fire Resistance	Not approved for use on Fire Doors
5	Safety	No Requirement
6	Corrosion Resistance	Very High 240 Hours Salt Spray (EN1670:1998)
7	Security	Very high security with Drilling Resistance
8	Field of Application	Mortice Lock for Hinged Doors
9	Type of Key	Lever Lock - Manual Latching
	Operation & Locking	
10	Type of Spindle	Sprung for Sprung Lever Furniture
	Operation	
11	Key Identification	Minimum 5 Levers

Kite Mark Liecence No. KM25285

Evidence of Standard Compliance

- Type Tested by Recognised Independent Test House Bodycote APT Laboratory
- Regular Audit Tested by Recognised Independent Test House Bodycote APT Laboratory

Evidence of Quality Control Compliance

 Manufacturer's Quality Control System to BS EN ISO 9001 : 2000 with Independent Quality Assessment

Evidence of Marking Compliance

• Kite Marked – BSI approved

K O'Reilly

Technical Director Signed on behalf of Securefast plc CE